



Reliable, compact and flexible modular UPS to best meet your needs.  
Ideal for single-phase critical loads in three-phase infrastructures.

 Telecom
  Datacom
  Mass transport
  Industry
  Power Utilities
  Renewable



## Description

Flexa 200 is a compact and modular UPS using a smart technology 3P input and 1P output. It provides a pure sine wave with **96%** conversion efficiency. Our technology offers a **0ms transfer time** (from grid to batteries), integrates the **static switch function, limited boost** capability (to trigger downstream breakers while protecting upstream ones) and is **easy to maintain** (24kg hot-swappable modules):



## Always powered

Flexa 200 operates **without master/slave** configuration, includes a **redundant communication BUS** and is IPC9592B certified. Efficient **battery management** makes it possible to always be ready to secure loads thanks to fast battery charging capacity (up to 17kW), low ripple voltage and different charging modes.

## Flexibility

Flexa 200 can be configured in 50Hz or 60Hz and also exists in 3P to 3P topology (Flexa 200 - 400/400). Cabinets can be **customized** on-demand, modules can be integrated into **third-party cabinets** or reused existing ones. Everything to be as flexible as possible.

## Applications

Flexa 200 is used in many applications to protect IT loads in datacenters and edge computing sites. Flexa 200 is also used and suitable for industrial, renewables, oil and gas, power utilities and in harsh environment (up to IP54).

### Key features:

- Flexibility
- 96% conversion efficiency
- Pure sine guaranteed
- Battery management
- Industrial design (up to IP54)
- Easy to maintain
- Compact and lightweight

Illustrations are non-binding and may include customized fittings.

# Flexa 200 - 400/230

	Module	40 kVA/kW	60 kVA/kW	80 kVA/kW	100 kVA/kW
<b>General</b>					
Module Part Number	T451970212				
EMC (immunity)	EN 61000-4-2 / EN 61000-4-3 / EN 61000-4-4 / EN 61000-4-5 / EN 61000-4-6 / EN 61000-4-8				
EMC (emission) (class)	EN 55022 (A)				
Safety	EN 62040-1-1				
EN62040-3 performance level	VFI-SS-111				
MTBF / Cooling	240 000 hrs / Forced				
True Redundant Systems – compliant	3 disconnection levels on AC out and DC in power ports / 4 disconnection levels on AC in port				
RoHS	Compliant				
Vibration	GR63 office vibration 0 to 100 Hz-0.1 g / transport vibration 5-100 Hz 0.5 g 100 to 500 Hz-1.5 g / Drop test				
Operating conditions	Designed for installation in an IP20 or IP21 environment. When installed in a dusty or corrosive environment, appropriate measures (air filtering, ...) must be taken.				
Altitude above sea without de-rating	< 1500 m / derating > 1500 m – 0.8 % per 100 m				
Ambient / storage temperature / relative humidity	-10 to 40 °C / -40 to 70 °C / 95%, non-condensing				
Material (casing)	Coated steel-ALU ZINC-Front plate coated black RAL9005				
<b>Power</b>					
<b>DC Input Data</b>					
Nominal voltage (DC)	408 Vdc (204 cells VRLA) or 336 cells (NiCd)				
Voltage range (DC)	336 Vdc to 490 Vdc				
<b>AC Input Data</b>					
Nominal voltage (AC)	3x380 / 400 / 415+Neutral 5 wires for 3 phases				
Voltage range (AC)	150 Vac to 275 Vac Line to Neutral (derating 150 to 220 Vac)				
Conformity range before transfer to DC	Adjustable				
Power factor	> 99%				
Frequency range / synchronization range	50 or 60 Hz (selectable) / range 30 to 70 Hz adjustable				
<b>AC Output Data</b>					
Efficiency (Typical): AC to AC / DC to AC	96% / 96% (certified by SGS at 45% load)				
Nominal voltage (AC*)	220 / 230 / 240 Vac single phase				
Frequency / frequency accuracy	50 - 60 Hz / 0.03 %				
Nominal Output power (VA) / (W)	20 kVA / 20 kW	40 kVA / 40 kW	60 kVA / 60 kW	80 kVA / 80 kW	100 kVA / 100 kW
Short time overload capacity	130 % (15 seconds) 110 % permanent within T° range				
Admissible load power factor	Full power rating from 0 inductive to 0 capacitive				
Total harmonic distortion (resistive load)	< 1.5 %				
Load impact recovery time	0.4 ms				
Turn on delay	20 s to 40 s depending on the number of module installed				
Nominal current at 230 Vac per phase	87 A	174 A	261 A	350 A	435 A
Crest factor at nominal power	3 : 1				
Short circuit clear up capacity	1.83 I <sub>n</sub> during 15 s and 1.41 I <sub>n</sub> after 15 s				
Internal temperature management and switch off	Yes				
<b>In Transfer Performance</b>					
Max. voltage interruption / total transient voltage duration (max)	0 s / 0 s				
<b>Signaling &amp; Supervision</b>					
Display	Synoptic LED				
Alarms output / supervision	Dry contacts on T4S / MODBUS, TCP-IP, SNMP				
Remote ON / OFF	On rear terminal of the shelf via T4S				
<b>Cabinets</b>					
Dimensions (WxHxD) with external MBP	19" x 3U x 515 mm		600 x 2100 x 800 mm		
Number of Cabinets	NA	1	1	1	1

\* Operation within lower voltage networks leads to de-rating of power performances.